

# 19" Wall Rack

## Characteristics of the 19" Wall Rack

- **Design:** 19" Wall Rack is designed three compartments, which consist of the front part, the middle part and the rear part. It is convenient to maintain.
- **Material:** The rack is made of 1.2 mm Electro-Galvanized Steel Sheet which is a thick, durable and 100% rustproof material.
- **Frames:** Vertical Mounted Frame is made of 2.0 mm Electro-Galvanized Steel Sheet which is a thick, durable and 100% rustproof material. It can be adjusted depending on the depth of the rack as requirement.
- **Roof:** The roof of rack can be installed the ventilating fan from 1 unit (standard) to 3 units (made to order).
- **Front Door:** The front door is 5 mm-transparency brown acrylic plastic which is thick and lightweight. It has a seal on the edge of the door to prevent dust. The front door has two Aluminum hinges and a turn-lock for security
- **Side Panel:** The side panel secures with a turn-lock and it is perforated to be well-ventilated.
- **Bottom Rack:** The bottom rack has a plate for covering and a hole with the dimensions 100 mm x 100 mm for putting cables through the hole. The additional ventilating fan can be installed at the bottom rack. (Optional)
- **Ground System:** There is the Ground System all parts of the rack with the earth cable kit.
- **Color:** The rack is a two-tone (light gray and dark gray) which is coated with powder epoxy by Electro-Static System for strength.
- **Accessories:** The rack is designed to provide customers with M6 bolts, cage nuts and plastic washers.
- **Quality Product Standard:** The racks meet quality product standards which are ANIS/EIA-310D-1992 (Rev.EIA-310-C), IEC 60297-1, IEC 60297-2, BS 5954: Part 2, DIN 41494.
- **Manufacturing standard:** ISO 9001: 2000 Company



## Illustration



Front View



Top View



Side View



Bottom View

## 19" Wall Rack

| u              | Height (mm.) | Height effective (mm.) | Order NO. (Width x Depth : mm.) |         |         |
|----------------|--------------|------------------------|---------------------------------|---------|---------|
| 1U = 44.45 mm. | H            | h                      | 600x400                         | 600x500 | 600x600 |
| 6U             | 350          | 290                    | PW-6406                         | PW-6506 | PW-6606 |
| 9U             | 485          | 425                    | PW-6509                         | PW-6509 | PW-6609 |
| 12U            | 620          | 560                    | PW-6412                         | PW-6512 | PW-6612 |

## Remark:

H= Height, h=Height Effective, W=Width, D=Depth

